

VICINITY MAP

IOWA DEPARTMENT OF NATURAL RESOURCES

CONSTRUCTION DOCUMENTS FOR LAKE GEODE SEDIMENT PONDS HENRY COUNTY, IOWA

PROJECT #14-06-44-01

LOCATION MAP



SHEET INDEX

SHEET. NO.	SHEET TITLE
1	COVER SHEET
2	LOCATION MAP
3	AREA 8 PLAN VIEW
4	AREA 8 CROSS SECTION
5	AREA 8 CANOPY DETAIL
6	AREA 8 SEEP COLLAR
7	AREA 2A PLAN VIEW
8	AREA 2A CROSS SECTION (6"PIPE)
9	AREA 2A CROSS SECTION (8"PIPE)
10	AREA 2A CANOPY DETAIL (6"PIPE)
11	AREA 2A 12" DIA. RISER DETAIL(8"PIPE)
12	AREA 2A SEEP COLLAR
13	AREA 2B PLAN VIEW
14	AREA 2B CROSS SECTION
15	AREA 2B LATERAL DETAIL
16	AREA 2B CANOPY DETAIL
17	AREA 2B SEEP COLLAR
18	AREA 7 PLAN VIEW
19	AREA 7 CROSS SECTION
20	AREA 7 CANOPY DETAIL
21	AREA 7 SEEP COLLAR
22	AREA 10 PLAN VIEW
23	AREA 10 CROSS SECTION
24	AREA 10 CANOPY DETAIL
25	AREA 10 SEEP COLLAR
26	AREA 12 PLAN VIEW
27	AREA 12 CROSS SECTION
28	AREA 12 CANOPY DETAIL
29	AREA 12 SEEP COLLAR
30	AREA 9 PLAN VIEW
31	AREA 9 CROSS SECTION
32	AREA 9 LATERAL DETAIL
33	AREA 9 CANOPY DETAIL
34	AREA 9 SEEP COLLAR

ESTIMATE OF QUANTITIES

ITEM NO.	DESCRIPTION	QUANTITY
1	MOBILIZATION	1 LS
2	6" DIA. SMOOTH STEEL PIPE	517 LF
3	8" DIA. SMOOTH STEEL PIPE	150 LF
4	10" DIA. SMOOTH STEEL PIPE	285 LF
5	12" DIA. SMOOTH STEEL PIPE	134 LF
6	12" DIA. RISER & BALLAST ELBOW (AREA 2A).	1 EA.
7	5' x 5' x 1/4" STEEL SEEP COLLAR	8 EA
8	6' x 6' x 1/4" STEEL SEEP COLLAR	11 EA
9	TRASH RACK / BAR GUARD ASSY. (6")	5 EA
10	TRASH RACK / BAR GUARD ASSY. (10")	1 EA
11	TRASH RACK / BAR GUARD ASSY. (12")	1 EA
12	EARTHWORK/ FILL/ GRADE	59,180 CY
13	SEED & MULCH	14 AC
14	CLEARING & GRUBBING	14 AC
15	CONSTRUCTION SURVEY & STAKING	1 LS
16	FARM – FIELD FENCE (WOVEN & BARB)	9010 LF
17	FARM – FIELD FENCE (NINE STRAND WIRE)	1900 LF
18	STEEL TUBE FARM GATE	4 EA.
19	IDOT CLASS "12" EXCAVATION	500 CY

NOTES:

12. BORROW MATERIAL FOR EMBANKMENT CONSTRUCTION WILL COME FROM WITHIN PERMANENT POOL AREA.
15. STAKING INFORMATION TO BE PROVIDED AT PRE–CONSTRUCTION CONFERENCE. MINOR BRANCH TRIMMING IS ALLOWED AND CONSIDERED INCIDENTAL TO THIS BID ITEM.

16 & 17 FIELD–FARM FENCE SHALL BE INSTALLED AROUND THE SEDIMENT BASINS AND TO REPAIR AREAS WHERE REMOVAL WAS NEEDED FOR ACCESS. SEE SPEC BOOK DETAILS

19. CONFIRM & COORDINATE CLASS 12 EXCAVATION MATERIAL WITH INSPECTOR PRIOR TO REMOVAL.

PROJECT DESCRIPTION

THIS PROJECT IS FOR THE CONSTRUCTION OF SEDIMENT BASINS AT LAKE GEODE, HENRY COUNTY.

IOWA ONE CALL
1-800-292-8989 | 811
www.iowaonecall.com
Know what's below. Call before you dig.

AUTHORIZATION TO BID

AUTHORIZATION - PARKS | WILDLIFE | FISHERIES | LAW ENFORCEMENT | FORESTRY DATE

ENGINEERING BUREAU CHIEF DATE

DIRECTORY

PROJECT MANAGER		CONSTRUCTION INSPECTOR	
	IOWA DEPARTMENT OF NATURAL RESOURCES		IOWA DEPARTMENT OF NATURAL RESOURCES
	502 EAST 9TH STREET		502 E. 9th STREET
	DES MOINES, IA, 50319		DES MOINES IA, 50319
	MIKE BRODERICK		HEATH DELZELL
	515-281-0873		515-979-0104
	mike.broderick@dnr.iowa.gov		heath.delzell@dnr.iowa.gov

IOWA DEPARTMENT OF NATURAL RESOURCES
ENGINEERING SERVICES - WALLACE BUILING
502 E. 9TH ST., DES MOINES, IA 50319-0034
P: 515.281.5918
F: 515.281.8685

COVER SHEET

GEODE SEDIMENT PONDS

HENRY COUNTY, IOWA

DANVILLE

NO.	BY DATE	REVISION

DRAWN BY: PROJECT NUMBER: 14-06-44-01

CHK'D BY: DATE: MAY 2014

SHEET No:



PROJECT SEDIMENT PONDS PROJ. NO. 14-06-44-01

AREA LAKE GEODE COUNTY HENRY

IA-313-A



0 1320 2640

Scale in Feet

If a cultural resource is identified during construction, stop immediately and notify the Natural Resources Conservation Service Archeologist at 515-284-4370

NRCS does not guarantee that this structure will fill and/or remain filled with water to the principal spillway crest elevation

CONTRACTOR IS RESPONSIBLE FOR CALLING IOWA ONE CALL 1-800-292-8989

All trees and shrubs shall be cleared and grubbed within a minimum distance of 30' from earthfill and spillway. New plantings shall not be made within these limitations.



AUXILIARY SPILLWAY
ELEVATION = 679.4
CONTROL SECTION = 25FT
BOTTOM WIDTH = 12 FT
BERM HEIGHT = 2.0 FT
BERM TOP WIDTH = 8 FT
BERM LENGTH = 50 FT
ENTRANCE SLOPE = 3%
EXIT SLOPE = 4%
SIDE SLOPES = 3:1

*NOTE
TBM 450 ⊙ S.W.
TBM = 697.90 / Top of Steel Rod

ENGINEERING JOB CLASS III

PLAN VIEW

75 0 75 150 225 300

SCALE IN FEET

N

Designed C. Waters 10/1/12
Drawn C. Waters 10/1/12
Traced C. Waters 10/1/12
Checked M. Allen 3/13

Approved D. Eisenhauer 4/13
Title District Conservationist

Title

U.S. DEPARTMENT OF AGRICULTURE – NATURAL RESOURCES CONSERVATION SERVICE

DA # 8 – Grade Stab. Park
Grade Stabilization – 410
Baltimore Twp Section 25
T70N – R5W – Henry Co. Iowa

CAD FILE NAME



2 - 72" x 72" Anti-seep collars
Length of pipe - 129 ft

SECTION ON CENTERLINE
Not to Scale

BILL OF MATERIALS

129 ft. of 6 " dia 14" ~~gage~~ Smooth metal pipe with ~~hood~~ Canopy inlet.
Pipe and appurtenances to be welded and water tight at the seams.

2 ea. antiseep collars 72" x 72", 14" ga. 2 piece.
Pipe connectors smooth metal

7,184 cu. yd. earth fill
Earthwork includes main fill, dike, core trench, wave berm (eye brow), and stripping.

Approved D. Ensminger 4/13 Title District Conservationist
Designed C. Waters 9/19/12
Drawn C. Waters 9/19/12
Traced C. Waters 9/19/12
Checked D. Ensminger 4/13



TBM = On top of Steel Rod @ Elev 697.90
(Note) TBM 950' Southwest of Site

CROSS-SECTION

~~HOOD~~ Canopy INLET
STANDARD DWG. NO. 713
REVISED SHEET 3 OF 3

Sec. 25 T 70N R 5W
County Howard
~~HOOD~~ Canopy INLET
Contractor DA#8 - Geode State Park
U.S. DEPARTMENT OF AGRICULTURE - NATURAL RESOURCES CONSERVATION SERVICE
Henry

NRCS does not guarantee that this structure will fill and/or remain filled with water to the principal spillway crest elevation



BENDING DIAGRAM FOR
(b) AND (c) RODS

BENDING DIAGRAM FOR
(d) BARS



BENDING DIAGRAM FOR
(a) RODS



ELEVATION



PLAN

Pipe Diam In.	Pipe Grade %	W In.	L In.	A Deg.	h Ft.
6	0-5	1 1/8	3 1/4	56	0.9
	5.1-15	1 1/4	4 3/4	45	0.9
	15.1-25	1 5/8	6 3/8	33	0.9
	25.1-32	2 1/8	7 3/4	27	0.9
8	0-5	1 1/2	4 3/8	56	1.2
	5.1-15	1 5/8	6 3/8	45	1.2
	15.1-25	2 1/8	8 3/4	33	1.2
	25.1-32	2 3/4	10 3/8	27	1.2
10	0-5	1 7/8	5 3/8	56	1.5
	5.1-15	2	8	45	1.5
	15.1-25	2 5/8	11	33	1.5
	25.1-32	3 1/2	13	27	1.5
12	0-5	2 1/4	6 1/2	56	1.8
	5.1-15	2 3/8	9 5/8	45	1.8
	15.1-25	3 1/4	13 1/4	33	1.8
	25.1-32	4 1/4	15 5/8	27	1.8
15	0-5	2 7/8	8 1/8	56	2.3
	5.1-15	3	12	45	2.3
	15.1-25	4	16 1/2	33	2.3
	25.1-32	5 1/4	19 1/2	27	2.3
18	0-5	3 3/8	9 3/4	56	2.7
	5.1-15	3 5/8	14 3/8	45	2.7
	15.1-25	4 7/8	19 3/4	33	2.7
	25.1-32	6 1/4	23 3/8	27	2.7
24	0-5	4 1/2	13	56	3.6
	5.1-15	4 3/4	19 1/4	45	3.6
	15.1-25	6 1/2	26 3/8	33	3.6
	25.1-32	8 3/8	31 1/4	27	3.6



DETAIL OF CANOPY INLET



* Minimum height for full pipe flow.

CANOPY INLET DIMENSIONS



PARTIAL ISOMETRIC VIEW

TABLE OF DIMENSION AND QUANTITIES

PIPE O.D. IN.	APPROX. WEIGHT LBS	(a) ROD SIZE IN.	H IN.	R IN.	X IN.	B IN.	TOTAL LENGTH IN.	NUMBER REQ'D	N IN.	(b) ROD SIZE IN.	r IN.	LENGTH IN.	NUMBER REQ'D	(c) ROD SIZE IN.	r IN.	LENGTH IN.	NUMBER REQ'D	(d) BAR SIZE IN.	r IN.	LENGTH IN.	NUMBER REQ'D
6	18.9	3/8	9	4	6	9 1/2	33	14	4	3/8	8 1/2	51 7/8	3	---	---	---	0	2 X 1/4	3 3/8	26 1/4	1
8	22.8	3/8	11	4 1/2	6	10 1/2	39	10	6 1/4	3/8	9 1/4	58 1/8	3	---	---	---	0	2 X 1/4	4 3/8	32 1/2	1
10	24.7	3/8	13	5 1/2	6	11 1/2	42	10	7	3/8	10 1/4	64 3/8	3	---	---	---	0	2 X 1/4	5 3/8	38 3/4	1
12	27.1	3/8	15	5 1/2	6	12 1/2	45	10	7 1/8	3/8	11 1/4	70 3/8	3	---	---	---	0	2 X 1/4	6 3/8	45	1
14	48.4	1/2	17	6	6	14	48	10	8 1/8	1/2	12	75 3/8	3	1/2	5	31 3/8	1	2 X 1/4	7 1/2	52 1/8	1
16	52.4	1/2	19	6 1/2	6	15	51	10	8 3/4	1/2	13	81 3/8	3	1/2	6	37 3/8	1	2 X 1/4	8 1/2	58 3/8	1
18	69.5	1/2	22	8 1/2	9	19 1/2	60	12	9 1/2	1/2	17	105 3/4	3	1/2	7	44	1	2 X 1/4	9 1/2	64 3/8	1
20	112.4	5/8	25	9	9	20 1/2	66	12	10	5/8	17 3/4	111 1/2	3	5/8	8	50 1/4	1	2 X 1/4	10 5/8	71 3/4	1
22	118.1	5/8	28	10	9	22	69	12	10 1/2	5/8	18 3/4	117 3/4	3	5/8	8	50 1/4	1	2 X 1/4	11 5/8	78	1
24	124.6	5/8	30	10 1/2	9	23	72	12	11	5/8	19 3/4	124	3	5/8	9 3/8	50 7/8	1	2 X 1/4	12 3/8	84 3/8	1

Design Area #8
Geode state Park
36 Baltimore T.70N R5W

U.S. DEPARTMENT OF AGRICULTURE
NATURAL RESOURCES CONSERVATION SERVICE

Designed C. Waters 9/11/12
Drawn C. Waters 9/14/12
Traced
Checked D.Ensminger 9/13
Approved by D.Ensminger DC

29L226



STEEL PLATE ANTI-SEEP COLLAR

NOTES:
1. All welds shall be watertight.
2. All steel plates shall have a minimum thickness of 1/4 ". Smooth Metal

4/04

NOT TO SCALE

Landowner:

STEEL PLATE
ANTI-SEEP COLLAR DETAILS
DA # 8

Date
Designed C. Waters
Drawn C. Waters
Checked MR Allen 3/3
Approved D. Ensminger 4/3

United States Department of Agriculture
NRCS Natural Resources Conservation Service

File Name
EA316loc12

Drawing Name
29-L-226

IA-313A



If a cultural resource is identified during construction, stop immediately and notify the Natural Resources Conservation Service Archeologist at 515-284-4370

NRCS does not guarantee that this structure will fill and/or remain filled with water to the principal spillway crest elevation

CONTRACTOR IS RESPONSIBLE FOR CALLING IOWA ONE CALL 1-800-292-8989

All trees and shrubs shall be cleared and grubbed within a minimum distance of 30' from earthfill and spillway. New plantings shall not be made within these limitations.

AUXILIARY SPILLWAY
ELEV = 690.9
CONTROL SECTION = 25 FT
BOTTOM WIDTH = 12 FT
BERM HEIGHT = 2.0 FT
BERM TOP WIDTH = 8FT
BERM LENGTH = 50FT
ENTRANCE SLOPE = 3%
EXIT SLOPE = 4%
SIDE SLOPES = 3:1

TBM Elev @ 702.4
On top of 1x2 Hub w/ Lath



PLAN VIEW

N

ENGINEERING JOB CLASS III

Approved D. Erstwayer 4/13
Title DC
Designed C. Waters 10/1/12
Drawn C. Waters 10/1/12
Traced C. Waters 10/1/12
Checked Mr. Allen 3/13

U.S. DEPARTMENT OF AGRICULTURE - NATURAL RESOURCES CONSERVATION SERVICE

DA#24 - Johnson
Grade Stabilization - 410
Danville Twp Section 31
T70-71 N Des Moines Co. Iowa

CAD FILE NAME

119.3



2 - 72" x 72" Anti-Seep Collars
Length of Pipe = 121.0 Ft

SECTION ON CENTERLINE

BILL OF MATERIALS

121 ft of 6 " x 1/4" pipe conforming to the [illegible] and specifications to be welded and water tight at the seams

2 [illegible] 72" x 72", 1/4" [illegible] 2 [illegible] smooth metal

7,960 [illegible] includes mainfill, dike, core trench, wave berm (eye brow), and stripping.



HOOD INLET

Cross Section

TBM 1 = Top of 1"X 2" HUB w/ Lath @ ELEV = 702.9
Located on fenceline North of Dam site

C. Waters 5/5/14
C. Waters 5/5/14
C. Waters 5/5/14
D Seemyer 5/5/14

31 20.4

HOOD INLET
Pottsville
Des Moines

DA # 2A - Johnson



SECTION ON CENTERLINE

BILL OF MATERIALS

10 ft. 12" dia. 1/4 gage metal pipe for riser. Fabricate with a 2' ft. stub of conduit attached at a 90.0° angle, ~~1'-1½" from the bottom. Antivortex device~~ x
"Drill 72-1" Holes Eft. in Top 8.0' of Riser"
150 ft. of 8 "dia. 1/4 gage metal pipe for conduit. Pipe and appurtenances to be Welded & water tight at Seams.

3 Antiseep collars 72" x 72", 2 piece.
Pipe connectors Smooth Metal

Earthwork 7960 Includes main fill, dike, Core trench, cut-outs mine burn & stripping

SEE SHEET 11 FOR INTAKE/RISER INFORMATION

B.M. Elev.

PIPE DROP INLET

Cooperator Johnson 2A
Sec. 3 L T. 72 R. 4
Des Moines County, Iowa

U. S. DEPARTMENT OF AGRICULTURE
SOIL CONSERVATION SERVICE

Designed C. Waters	Date 5/6/11	Approved by D. Fosenaugh	
Drawn C. Waters	5/6/11	Title DC	
Traced C. Waters	5/6/11	Title	
Checked D. Fosenaugh	5/6/11	Sheet No. 9 of 10 sheets	Drawing No. 9 of 34

USDA-SCS-STACCLK, Rev. 1965

ORDER THIS BLANK DATA SHEET BY DRAWING NUMBER 5-K-21.082



BENDING DIAGRAM FOR
(b) AND (c) RODS

BENDING DIAGRAM FOR
(d) BARS

Pipe Diam. In.	Pipe Grade X	W In.	L In.	∠ Deg.	h Ft.
6	0-5	1 1/8	3 1/4	56	0.9
	5.1-15	1 1/4	4 3/4	45	0.9
	15.1-25	1 5/8	6 5/8	33	0.9
	25.1-32	2 1/8	7 3/4	27	0.9
8	0-5	1 1/2	4 3/8	56	1.2
	5.1-15	1 5/8	6 3/8	45	1.2
	15.1-25	2 1/8	8 3/4	33	1.2
	25.1-32	2 3/4	10 3/8	27	1.2
10	0-5	1 7/8	5 3/8	56	1.5
	5.1-15	2	8	45	1.5
	15.1-25	2 5/8	11	33	1.5
	25.1-32	3 1/2	13	27	1.5
12	0-5	2 1/4	6 1/2	56	1.8
	5.1-15	2 3/8	9 5/8	45	1.8
	15.1-25	3 1/4	13 1/4	33	1.8
	25.1-32	4 1/4	15 5/8	27	1.8
15	0-5	2 7/8	8 1/8	56	2.3
	5.1-15	3	12	45	2.3
	15.1-25	4	16 1/2	33	2.3
	25.1-32	5 1/4	19 1/2	27	2.3
18	0-5	3 3/8	9 3/4	56	2.7
	5.1-15	3 5/8	14 3/8	45	2.7
	15.1-25	4 7/8	19 3/4	33	2.7
	25.1-32	6 1/4	23 3/8	27	2.7
24	0-5	4 1/2	13	56	3.6
	5.1-15	4 3/4	19 1/4	45	3.6
	15.1-25	6 1/2	26 3/8	33	3.6
	25.1-32	8 3/8	31 1/4	27	3.6



DETAIL OF CANOPY INLET



* Minimum height for full pipe flow.

CANOPY INLET DIMENSIONS



PARTIAL ISOMETRIC VIEW



BENDING DIAGRAM FOR
(a) RODS



ELEVATION



PLAN

TABLE OF DIMENSION AND QUANTITIES

PIPE O.D. IN.	APPROX. WEIGHT LBS	(a) ROD SIZE IN.	H IN.	R IN.	X IN.	θ IN.	TOTAL LENGTH IN.	NUMBER REQ'D	N IN.	(b) ROD SIZE IN.	r IN.	LENGTH IN.	NUMBER REQ'D	(c) ROD SIZE IN.	r IN.	LENGTH IN.	NUMBER REQ'D	(d) BAR SIZE IN.	r IN.	LENGTH IN.	NUMBER REQ'D
6	18.2	3/8	9	4	6	9 1/2	33	14	4	3/8	8 1/4	51 1/8	3	---	---	---	0	2 X 1/4	5 3/8	25 1/8	1
8	22.8	3/8	11	4 1/2	6	10 1/8	39	10	6 1/4	3/8	9 1/4	58 1/8	3	---	---	---	0	2 X 1/4	4 3/8	32 1/8	1
10	24.7	3/8	13	5 1/2	6	11 1/2	42	10	7	3/8	10 1/4	64 3/8	3	---	---	---	0	2 X 1/4	5 3/8	38 3/8	1
12	27.1	3/8	15	3 1/2	6	12 1/2	45	10	7 1/8	3/8	11 1/4	70 3/8	3	---	---	---	0	2 X 1/4	6 3/8	45	1
14	38.4	1/2	17	6	6	14	48	10	8 1/8	1/2	12	75 3/8	3	1/2	5	31 3/8	1	2 X 1/4	7 1/2	52 1/8	1
16	58.4	1/2	19	6 1/2	6	15	51	10	8 3/4	1/2	13	81 3/8	3	1/2	6	37 3/8	1	2 X 1/4	8 1/2	58 3/8	1
18	69.5	1/2	22	8 1/2	9	19 1/2	60	12	9 1/2	1/2	17	106 3/4	3	1/2	7	44	1	2 X 1/4	9 1/2	64 3/8	1
20	118.4	5/8	28	9	9	20 1/2	66	12	10	5/8	17 3/4	111 1/8	3	5/8	8	50 3/4	1	2 X 1/4	10 3/8	71 3/4	1
22	110.1	5/8	28	10	9	22	69	12	10 1/2	5/8	18 3/4	117 3/4	3	5/8	8	50 3/4	1	2 X 1/4	11 3/8	78	1
24	124.6	5/8	30	10 1/2	9	23	72	12	11	5/8	19 3/4	124	3	5/8	9 3/8	58 1/8	1	2 X 1/4	12 3/8	84 1/8	1

DA # 2A ~ Johnson
31 Danville T16-21N R4W

U.S. DEPARTMENT OF AGRICULTURE
NATURAL RESOURCES CONSERVATION SERVICE

designed B Waters 10/12
drawn C Waters 10/12
traced
checked DEnsminger 11/13
approved by DEnsminger
title DE
date

10 of 34



OPERATION AND MAINTENANCE REQUIREMENTS

1. Periodic inspections, especially immediately following significant runoff events, to keep inlets, trash guards, and collection boxes and structures clean and free of materials that can reduce flow.
2. Prompt repair or replacement of damaged components.
3. Repair or replacement of inlets damaged by farm equipment.
4. Repair of leaks and broken or crushed lines to insure proper functioning of the conduit.
5. Periodic checking of the outlet and animal guards to ensure proper functioning.
6. Repair of eroded areas at the pipe outlet.
7. Maintain adequate backfill over the conduit.
8. Control weeds, brush, and trees that could impact the flow or function of the underground outlet by mechanical methods or chemicals

12" Riser on 8" Pipe with 2' Below Elbow For Ballast
All ¼" Smooth metal 72 - 1" Holes / Ft. In Top 8'
Place Bird Cage on Top of Riser
Offset Not Required

STANDARD DWG. IA-1501

DATE Oct. 2008 | PAGE 1 OF 2

NRCS
Natural Resources Conservation Service
United States Department of Agriculture

UNDERGROUND OUTLET

Owner: Johnson
Location: Sec 31, T 76 N, R 4 W
Deaville Township
Des Moines County, Iowa

		Date
Designed	C. Waters	5/5/14
Drawn	C. Waters	5/5/14
Checked	C. Waters	5/5/14
Approved	D Erstmeyer	5/6/14

File Name

Drawing Name

291-226



STEEL PLATE ANTI-SEEP COLLAR

NOTES:
1. All welds shall be watertight.
2. All steel plates shall have a minimum thickness of 1/4 ". Smooth Metal

4/04

NOT TO SCALE

Landowner:

STEEL PLATE
ANTI-SEEP COLLAR DETAILS
DA # 2A (Johnson)

Date
Designed C. Waters
Drawn C. Waters
Checked M. Allred 3/15
Approved D. Brannon 4/15

United States Department of Agriculture
Natural Resources Conservation Service
NRCS

File Name
IA346100112

Drawing Name
29-L-226

IA-313-A





If a cultural resource is identified during construction, stop immediately and notify the Natural Resources Conservation Service Archeologist at 515-284-4370

NRCS does not guarantee that this structure will fill and/or remain filled with water to the principal spillway crest elevation

CONTRACTOR IS RESPONSIBLE FOR CALLING IOWA ONE CALL 1-800-292-8989

All trees and shrubs shall be cleared and grubbed within a minimum distance of 30' from earthfill and spillway. New plantings shall not be made within these limitations.





PLAN VIEW

ENGINEERING JOB CLASS III

	Date	Designed	Date	Drawn	Date	Traced	Date	Checked
		C. Waters	10/1/12	C. Waters	10/1/12	C. Waters	10/1/12	M. Allen 3/13

Approved ..... Title .....
Approved ..... Title .....

U.S. DEPARTMENT OF AGRICULTURE – NATURAL RESOURCES CONSERVATION SERVICE

DA#28 - Johnson
Grade Stabilization - 4/10
Danville TWP Section 31
T70-11N Des Moines Co. Iowa

CAD FILE NAME



SECTION ON CENTERLINE

Not to Scale

BILL OF MATERIALS

142 ft. of 10 " dia 14 gage metal pipe with ~~hood~~ Canopy inlet.
Pipe and appurtenances to be welded and water tight at the seams.

3 ea. antiseep collars 60" x 60", 14 ga. 2 piece.
Pipe connectors smooth metal

10,208 cu. yd. earth fill
Earthwork includes mainfill, dike, core trench, wave berm (eye brow), and stripping.

Designed	C. Waters	10/13
Drawn	C. Waters	10/13
Traced	C. Waters	10/13
Checked	Mc Allen	9/13



CROSS SECTION

TBM = 702.40
Location 420' North, on top of 1x2 Hub/Lath

Canopy STANDARD DRAWING
~~HOOD~~ INLET
STANDARD DWG. NO. 715
SHEET 4 OF 4

Sec. 31 T6N R4W
Canopy HOOD INLET
Designed Des Moines County, Iowa
DA #28 - Johnson
U.S. DEPARTMENT OF AGRICULTURE - NATURAL RESOURCES CONSERVATION SERVICE

NRCS does not guarantee that this structure will fill and/or remain filled with water to the principal spillway crest elevation


LATERAL F
LATERAL G
LATERAL E
LATERAL A
LATERAL C
LATERAL D
NATURAL GROUND
LATERAL B
℄ FILL
AUXILIARY SPILLWAY ELEV. = 683.3
PIPE OUTLET ELEV. 661.5
CORE TRENCH
BOTTOM WIDTH = 12 FT.
SIDE SLOPES = 1.5:1
MINIMUM DEPTH = 4.0 FT.
AND TO SUITABLE MATERIAL
DOWNSTREAM TOE ELEV. = 660.5
680.0
670.0
660.0
10+00
7+50
5+00
2+50
0+00
PROFILE
NRCS does not guarantee that this structure will fill and/or remain filled with water to the principal spillway crest elevation
Designed C. Waters 3/25/13
Drawn C. Waters 3/25/13
Traced C. Waters
Quantities D. Ernzinger 4/13
DA # 26 - Johnson
Grade Stabilization - 410
Danville Twp Section 31
T70-71N Des Moines Co. Iowa
U.S. DEPARTMENT OF AGRICULTURE - NATURAL RESOURCES CONSERVATION SERVICE



BENDING DIAGRAM FOR
(b) AND (c) RODS

BENDING DIAGRAM FOR
(d) BARS

Pipe Diam. In.	Pipe Grade X	W In.	L In.	A Deg.	h Ft.
6	0-5	1 1/8	3 1/4	56	0.9
	5.1-15	1 1/4	4 3/4	45	0.9
	15.1-25	1 5/8	6 5/8	33	0.9
	25.1-32	2 1/8	7 3/4	27	0.9
8	0-5	1 1/2	4 3/8	56	1.2
	5.1-15	1 5/8	6 3/8	45	1.2
	15.1-25	2 1/8	8 3/4	33	1.2
	25.1-32	2 3/4	10 3/8	27	1.2
10	0-5	1 7/8	5 3/8	56	1.5
	5.1-15	2	8	45	1.5
	15.1-25	2 5/8	11	33	1.5
	25.1-32	3 1/2	13	27	1.5
12	0-5	2 1/4	6 1/2	56	1.8
	5.1-15	2 3/8	9 5/8	45	1.8
	15.1-25	3 1/4	12 1/4	33	1.8
	25.1-32	4 1/4	15 5/8	27	1.8
15	0-5	2 7/8	8 1/8	56	2.3
	5.1-15	3	12	45	2.3
	15.1-25	4	16 1/2	33	2.3
	25.1-32	5 1/4	19 1/2	27	2.3
18	0-5	3 3/8	9 3/4	56	2.7
	5.1-15	3 5/8	14 3/8	45	2.7
	15.1-25	4 7/8	19 3/4	33	2.7
	25.1-32	6 1/4	23 3/8	27	2.7
24	0-5	4 1/2	13	56	3.6
	5.1-15	4 3/4	19 1/4	45	3.6
	15.1-25	6 1/2	26 3/8	33	3.6
	25.1-32	8 3/8	31 1/4	27	3.6



DETAIL OF CANOPY INLET



* Minimum height for full pipe flow.

CANOPY INLET DIMENSIONS



BENDING DIAGRAM FOR
(a) RODS



ELEVATION



PLAN



PARTIAL ISOMETRIC VIEW

TABLE OF DIMENSION AND QUANTITIES

PIPE O.D. IN.	APPROX. WEIGHT LBS	(a) ROD SIZE IN.	H IN.	R IN.	X IN.	D IN.	TOTAL LENGTH IN.	NUMBER REQ'D	N IN.	(b) ROD SIZE IN.	r IN.	LENGTH IN.	NUMBER REQ'D	(c) ROD SIZE IN.	r IN.	LENGTH IN.	NUMBER REQ'D	(d) BAR SIZE IN.	r IN.	LENGTH IN.	NUMBER REQ'D
6	18.9	3/8	9	4	6	9 1/2	33	14	4	3/8	8 1/4	51 7/8	3	---	---	---	0	2 X 1/4	5 3/8	26 1/4	1
8	22.3	3/8	11	4 1/2	6	10 1/2	39	10	6 1/4	3/8	9 1/4	58 1/8	3	---	---	---	0	2 X 1/4	14 3/8	32 1/2	1
10	24.7	3/8	13	5 1/2	6	11 1/2	42	10	7	3/8	10 1/4	64 3/8	3	---	---	---	0	2 X 1/4	5 3/8	38 3/4	1
12	27.1	3/8	15	5 1/2	6	12 1/2	45	10	7 1/8	3/8	11 1/4	70 3/8	3	---	---	---	0	2 X 1/4	6 3/8	45	1
14	48.4	1/2	17	6	6	14	48	10	8 1/8	1/2	12	75 3/8	3	1/2	5	31 3/8	1	2 X 1/4	7 1/2	52 1/8	1
16	52.4	1/2	19	6 1/2	6	15	51	10	8 3/4	1/2	13	81 3/8	3	1/2	6	37 3/8	1	2 X 1/4	8 1/2	58 3/8	1
18	69.5	1/2	22	8 1/2	9	19 1/2	60	12	9 1/8	1/2	17	106 3/4	3	1/2	7	44	1	2 X 1/4	9 1/2	64 3/8	1
20	112.4	5/8	25	9	9	20 1/2	66	12	10	5/8	17 3/4	111 1/2	3	5/8	8	50 1/4	1	2 X 1/4	10 3/8	71 3/4	1
22	118.1	5/8	28	10	9	22	69	12	10 1/2	5/8	18 3/4	117 3/4	3	5/8	8	50 1/4	1	2 X 1/4	11 5/8	78	1
24	124.6	5/8	30	10 1/2	9	23	72	12	11	5/8	19 3/4	124	3	5/8	9 3/8	58 7/8	1	2 X 1/4	12 5/8	84 3/8	1

DA#28- Johnson
31 Danville T70-71N R5W

U.S. DEPARTMENT OF AGRICULTURE
NATURAL RESOURCES CONSERVATION SERVICE

Designed C. Waters 10/31/12
Drawn C. Waters 10/31/12
Traced
Checked D. Erickson 11/2/12
Approved by
Title
Date
Sheet No. 5 of 5

29L226



STEEL PLATE ANTI-SEEP COLLAR

NOTES:
1. All welds shall be watertight.
2. All steel plates shall have a minimum thickness of 1/4 ". Smooth Metal

4/04

NOT TO SCALE

Landowner:

Designed	C. Walters 3/13
Drawn	C. Walters 3/13
Checked	M. Allred 3/13
Approved	Designer 3/13

STEEL PLATE
ANTI-SEEP COLLAR DETAILS
DA # 2 B (Johnson)

United States Department of Agriculture
Natural Resources Conservation Service
NRCS

File Name
IA346100112

Drawing Name
29-L-226

IA-313-A



0 1320 2640

Scale in Feet

If a cultural resource is identified during construction, stop immediately and notify the Natural Resources Conservation Service Archeologist at 515-284-4370

NRCS does not guarantee that this structure will fill and/or remain filled with water to the principal spillway crest elevation

CONTRACTOR IS RESPONSIBLE FOR CALLING IOWA ONE CALL 1-800-292-8989

All trees and shrubs shall be cleared and grubbed within a minimum distance of 30' from earthfill and spillway. New plantings shall not be made within these limitations.

AUXILIARY SPILLWAY
ELEV: 665.3
CONTROL SECTION = 25 FT
BOTTOM WIDTH = 12 FT
BERM HEIGHT = 2.0 ft
BERM TOP WIDTH = 8 ft
BERM LENGTH = 50 ft
ENTRANCE SLOPE = 3%
EXIT SLOPE = 4%
SIDE SLOPES = 3:1



50 0 50 100 150 200

SCALE IN FEET

N

ENGINEERING JOB CLASS III

PLAN VIEW

Designed C. Waters 9/19/12
Drawn C. Waters 9/19/12
Traced C. Waters 9/19/12
Checked M. Allen 9/13

Approved Doug Ensminger 11/3
Title District Conservationist

Title

U.S. DEPARTMENT OF AGRICULTURE - NATURAL RESOURCES CONSERVATION SERVICE

DA # 7 - Goode State Park
Grade Stabilization - 410
Baltimore TWP Section 25
T70N - R5W - Henry Co. Iowa

CAD FILE NAME



2- 60" x 60" Anti-seep Collars
Length of pipe - 127ft

SECTION ON CENTERLINE
Not to Scale

BILL OF MATERIALS

127 ft. of 6 " dia 14" ~~gage~~ Smooth metal pipe with ~~hood~~ canopy inlet.
Pipe and appurtenances to be welded and water tight at the seams.

2 ea. antiseep collars 60" x 60", 14" ga. 2 piece.
Pipe connectors smooth metal

5,945 cu. yd. earth fill
Earthwork includes maintill, dike, core trench, wave berm (eye) brow, and stripping

Designed C. Waters 9/11/12 Approved D. Kramer, NRCS
Drawn C. Waters 9/11/12 Title District Conservationist
Traced C. Waters 9/11/12
Checked [signature] 9/13 Title



Cross Section

TBM1: On top of Steel Rod @ Elev 697.90
Located directly South of Site

NRCS does not guarantee that this structure will fill and/or remain filled with water to the principal spillway crest elevation

Canopy STANDARD DRAWING
~~HOOD~~ INLET
STANDARD DWG. NO. 715
REVISED: | SHEET 1 OF 1

Canopy ~~HOOD~~ INLET

Sec 35 T70N R5W
County Henry
Cooperator DA #7 - Geode State Park
U.S. DEPARTMENT OF AGRICULTURE - NATURAL RESOURCES CONSERVATION SERVICE
NO SCALE



BENDING DIAGRAM FOR (b) AND (c) RODS

BENDING DIAGRAM FOR (d) BARS



BENDING DIAGRAM FOR (a) RODS



ELEVATION

Pipe Diam. In.	Pipe Grade %	W In.	L In.	A Deg.	h Ft.
6	0-5	1 1/8	3 1/4	56	0.9
	5.1-15	1 1/4	4 3/4	45	0.9
	15.1-25	1 5/8	6 5/8	33	0.9
	25.1-32	2 1/8	7 3/4	27	0.9
8	0-5	1 1/2	4 3/8	56	1.2
	5.1-15	1 5/8	6 3/8	45	1.2
	15.1-25	2 1/8	8 3/4	33	1.2
	25.1-32	2 3/4	10 3/8	27	1.2
10	0-5	1 7/8	5 3/8	56	1.5
	5.1-15	2	8	45	1.5
	15.1-25	2 5/8	11	33	1.5
	25.1-32	3 1/2	13	27	1.5
12	0-5	2 1/4	6 1/2	56	1.8
	5.1-15	2 3/8	9 5/8	45	1.8
	15.1-25	3 1/4	13 1/4	33	1.8
	25.1-32	4 1/4	15 5/8	27	1.8
15	0-5	2 7/8	8 1/8	56	2.3
	5.1-15	3	12	45	2.3
	15.1-25	4	16 1/2	33	2.3
	25.1-32	5 1/4	19 1/2	27	2.3
18	0-5	3 3/8	9 3/4	56	2.7
	5.1-15	3 5/8	14 3/8	45	2.7
	15.1-25	4 7/8	19 3/4	33	2.7
	25.1-32	6 1/4	23 3/8	27	2.7
24	0-5	4 1/2	13	56	3.6
	5.1-15	4 3/4	19 1/4	45	3.6
	15.1-25	6 1/2	26 3/8	33	3.6
	25.1-32	8 3/8	31 1/4	27	3.6



PLAN



DETAIL OF CANOPY INLET



* Minimum height for full pipe flow.

CANOPY INLET DIMENSIONS



PARTIAL ISOMETRIC VIEW

TABLE OF DIMENSION AND QUANTITIES

PIPE O.D. IN.	APPROX. WEIGHT LBS	(a) ROD SIZE IN.	H IN.	R IN.	X IN.	D IN.	TOTAL LENGTH IN.	NUMBER REQ'D	N IN.	(b) ROD SIZE IN.	r IN.	LENGTH IN.	NUMBER REQ'D	(c) ROD SIZE IN.	r IN.	LENGTH IN.	NUMBER REQ'D	(d) BAR SIZE IN.	r IN.	LENGTH IN.	NUMBER REQ'D
6	18.9	3/8	9	4	6	9 1/2	33	14	4	3/8	8 1/4	51 7/8	3	---	---	---	0	2 x 1/4	3 3/8	26 1/4	1
8	22.8	3/8	11	4 1/2	6	10 1/2	39	10	6 1/4	3/8	9 1/4	59 3/8	3	---	---	---	0	2 x 1/4	4 3/8	32 1/8	1
10	24.7	3/8	13	5 1/2	6	11 1/2	42	10	7	3/8	10 1/4	64 3/8	3	---	---	---	0	2 x 1/4	5 3/8	38 3/4	1
12	27.1	3/8	15	5 1/2	6	12 1/2	45	10	7 1/2	3/8	11 1/4	70 3/8	3	---	---	---	0	2 x 1/4	6 3/8	45	1
14	48.4	1/2	17	6	6	14	48	10	8 1/8	1/2	12	75 3/8	3	1/2	5	31 3/8	1	2 x 1/4	7 1/2	52 1/8	1
16	52.4	1/2	19	6 1/2	6	15	51	10	8 3/4	1/2	13	81 3/8	3	1/2	6	37 3/8	1	2 x 1/4	8 1/2	58 3/8	1
18	69.5	1/2	22	8 1/2	9	19 1/2	60	12	9 1/2	1/2	17	106 3/4	3	1/2	7	44	1	2 x 1/4	9 1/2	64 5/8	1
20	112.4	5/8	25	9	9	20 1/2	66	12	10	5/8	17 3/4	111 3/8	3	5/8	8	50 1/4	1	2 x 1/4	10 3/8	71 3/4	1
22	118.1	5/8	28	10	9	22	69	12	10 1/2	5/8	18 3/4	117 3/4	3	5/8	8	50 1/4	1	2 x 1/4	11 3/8	78	1
24	124.6	5/8	30	10 1/2	9	23	72	12	11	5/8	19 3/4	124	3	5/8	9 3/8	58 7/8	1	2 x 1/4	12 3/8	84 3/8	1

Design Area #7
Geode state Park
25 Baltimore T70N. R5W

U.S. DEPARTMENT OF AGRICULTURE
NATURAL RESOURCES CONSERVATION SERVICE

Designed C. Waters 9/11 Approved by [illegible]
Drawn C. Waters 9/11 Title
Traced
Checked [illegible] 4/12 Title Sheet No. 3 of 4

29L226



STEEL PLATE ANTI-SEEP COLLAR

NOTES:
1. All welds shall be watertight.
2. All steel plates shall have a minimum thickness of 1/4 ". Smooth Metal

4/04

NOT TO SCALE

Landowner:

STEEL PLATE
ANTI-SEEP COLLAR DETAILS
DA #7

Designed C. Wakers 10/18/12
Drawn C. Wakers 10/18/12
Checked DeShawn 10/19/12
Approved DeShawn 10/19/12

United States Department of Agriculture
Natural Resources Conservation Service
NRCS

File Name
IA346091912

Drawing Name
29-L-226

IA-313-A

BALTIMORE TWP T70N R5W
SECTION 25



0 1320 2640

Scale in Feet

If a cultural resource is identified during construction, stop immediately and notify the Natural Resources Conservation Service Archeologist at 515-284-4370

NRCS does not guarantee that this structure will fill and/or remain filled with water to the principal spillway crest elevation

CONTRACTOR IS RESPONSIBLE FOR CALLING IOWA ONE CALL 1-800-292-8989

All trees and shrubs shall be cleared and grubbed within a minimum distance of 30' from earthfill and spillway. New plantings shall not be made within these limitations.



50 0 50 100 150 200

SCALE IN FEET

N

PLAN VIEW

ENGINEERING JOB CLASS III

Designed	C. Waters	9/97	Date
Drawn	C. Waters	11/97	Date
Traced	L. Waters	11/97	Date
Checked	M. Allen	9/98	Date
Approved	Designer	9/98	Date
Title	DC		
Title			

U.S. DEPARTMENT OF AGRICULTURE - NATURAL RESOURCES CONSERVATION SERVICE

DA # 10 - Reid.
Grade Stabilization - 410
Baltimore TWP Section 25
T70N-R5W Henry Co. Iowa.

CAD FILE NAME



2- 72" x 72" Anti-seep collars
Length of pipe = 140 ft.

SECTION ON CENTERLINE

Not to Scale

BILL OF MATERIALS

140 ft. of 6 " dia 14" ~~gage~~ Smooth metal pipe with ~~hood~~ canopy inlet.
Pipe and appurtenances to be welded and water tight at the seams.

2 ea. antiseep collars 72" x 72" 14" ga. 2 piece.
Pipe connectors smooth metal

7,836 cu. yd. earth fill
Earthwork includes main fill, dike, core trench, ware berm (eye brow), and stripping.

Approved D. Erasmus 9/13
Title DC
Designed C. Waters 9/19/12
Drawn C. Waters 9/19/12
Traced C. Waters 9/19/12
Checked D. Erasmus 9/13
Date
Title

690
680
670
660
650

Cross Section + Pipe

Cross Section + Pipe
Elev = 676.9
Top of constructed Fill

Settled Fill Elev @ 674.5

Crest Elev = 670

AUXILARY SPILLWAY
BOTTOM WIDTH = 12'
ELEVATION = 672.3
SIDE SLOPE = 3:1
25 FT CONTROL SECTION
DIKE LENGTH = 50 FT
DIKE HEIGHT = 2 FT
DIKE TOP WIDTH = 8FT
ENTRANCE SLOPE = 3%
EXIT SLOPE = 4%

CORE TRENCH
BOTTOM WIDTH = 12'
SIDE SLOPES = 1.5:1
MINIMUM DEPTH = 4 FT
AND TO SUITABLE MATERIAL

0+00
1+00
2+00
3+00

B.M. Elev

Cross Section

TBM1 = On top of Steel Rod @ Elev 701.3
Located in Fenceline east of Dam/Spillway

NRCS does not guarantee that this structure will fill and/or remain filled with water to the principal spillway crest elevation

Canopy HOOD INLET
STANDARD DWG. NO. 713
REVISED SHEET 1 OF 1

Sec 25 T6N R5W
Henry County, Iowa

USDA NATURAL RESOURCES CONSERVATION SERVICE
DEPARTMENT OF AGRICULTURE

Canopy HOOD INLET
DA # 10 (Reid)

ADD FILE NAME



BENDING DIAGRAM FOR (b) AND (c) RODS

BENDING DIAGRAM FOR (d) BARS



BENDING DIAGRAM FOR (a) RODS



ELEVATION



PLAN

Pipe Diam. In.	Pipe Grade %	W In.	L In.	A Deg.	h Ft.
6	0-5	1 1/8	3 1/4	56	0.9
	5.1-15	1 1/4	4 3/4	45	0.9
	15.1-25	1 5/8	6 5/8	33	0.9
	25.1-32	2 1/8	7 3/4	27	0.9
8	0-5	1 1/2	4 3/8	56	1.2
	5.1-15	1 5/8	6 3/8	45	1.2
	15.1-25	2 1/8	8 3/4	33	1.2
	25.1-32	2 3/4	10 3/8	27	1.2
10	0-5	1 7/8	5 3/8	56	1.5
	5.1-15	2	8	45	1.5
	15.1-25	2 5/8	11	33	1.5
	25.1-32	3 1/2	13	27	1.5
12	0-5	2 1/4	6 1/2	56	1.8
	5.1-15	2 3/8	9 5/8	45	1.8
	15.1-25	3 1/4	13 1/4	33	1.8
	25.1-32	4 1/4	15 5/8	27	1.8
15	0-5	2 7/8	8 1/8	56	2.3
	5.1-15	3	12	45	2.3
	15.1-25	4	16 1/2	33	2.3
	25.1-32	5 1/4	19 1/2	27	2.3
18	0-5	3 3/8	9 3/4	56	2.7
	5.1-15	3 5/8	14 3/8	45	2.7
	15.1-25	4 7/8	19 3/4	33	2.7
	25.1-32	6 1/4	23 3/8	27	2.7
24	0-5	4 1/2	13	56	3.6
	5.1-15	4 3/4	19 1/4	45	3.6
	15.1-25	6 1/2	26 3/8	33	3.6
	25.1-32	8 3/8	31 1/4	27	3.6



DETAIL OF CANOPY INLET



* Minimum height for full pipe flow

CANOPY INLET DIMENSIONS



PARTIAL ISOMETRIC VIEW

TABLE OF DIMENSION AND QUANTITIES

PIPE O.D. IN.	APPROX. WEIGHT LBS	(a) ROD SIZE IN.	H IN.	R IN.	X IN.	D IN.	TOTAL LENGTH IN.	NUMBER REQ'D	N IN.	(b) ROD SIZE IN.	r IN.	LENGTH IN.	NUMBER REQ'D	(c) ROD SIZE IN.	r IN.	LENGTH IN.	NUMBER REQ'D	(d) BAR SIZE IN.	r IN.	LENGTH IN.	NUMBER REQ'D
6	18.9	3/8	9	4	6	9 1/2	33	14	4	3/8	8 1/2	51 7/8	3	---	---	---	0	2 X 1/4	3 3/8	26 1/4	1
8	22.8	3/8	11	4 1/2	6	10 1/2	39	10	6 1/4	3/8	9 1/4	58 1/8	3	---	---	---	0	2 X 1/4	4 3/8	32 1/2	1
10	24.7	3/8	13	5 1/2	6	11 1/2	42	10	7	3/8	10 1/4	64 3/4	3	---	---	---	0	2 X 1/4	5 3/8	38 3/4	1
12	27.1	3/8	15	5 1/2	6	12 1/2	45	10	7 1/8	3/8	11 1/4	70 5/8	3	---	---	---	0	2 X 1/4	6 3/8	45	1
14	48.4	1/2	17	6	6	14	48	10	8 1/8	1/2	12	75 3/8	3	1/2	5	31 3/8	1	2 X 1/4	7 1/2	52 1/8	1
16	52.4	1/2	19	6 1/2	6	15	51	10	8 3/4	1/2	13	81 3/8	3	1/2	6	37 5/8	1	2 X 1/4	8 1/2	58 3/8	1
18	69.5	1/2	22	8 1/8	9	19 1/2	60	12	9 1/2	1/2	17	106 3/4	3	1/2	7	44	1	2 X 1/4	9 1/2	64 5/8	1
20	112.4	5/8	25	9	9	20 1/2	66	12	10	5/8	17 3/4	111 1/2	3	5/8	8	50 1/4	1	2 X 1/4	10 3/8	71 3/4	1
22	118.1	5/8	28	10	9	22	69	12	10 1/2	5/8	18 3/4	117 3/4	3	5/8	8	50 1/4	1	2 X 1/4	11 3/8	78	1
24	124.6	5/8	30	10 1/2	9	23	72	12	11	5/8	19 3/4	124	3	5/8	9 3/8	58 7/8	1	2 X 1/4	12 3/8	84 1/8	1

Reid Site #10
Grade Stabilization - 410
25 - Baltimore T.70N R5W

U.S. DEPARTMENT OF AGRICULTURE
NATURAL RESOURCES CONSERVATION SERVICE

Designed C. Waters 9/19/12 — Approved by D. Erasmayer
Drawn C. Waters 9/19/12 — Title PE
Traced C. Waters 9/19/12 — Title
Checked D. Erasmayer 9/19/12 — Sheet No. 3 of 4

291 226



STEEL PLATE ANTI-SEEP COLLAR

NOTES:
1. All welds shall be watertight.
2. All steel plates shall have a minimum thickness of 1/4 ". Smooth Metal

4/04

NOT TO SCALE

Landowner:

STEEL PLATE
ANTI-SEEP COLLAR DETAILS
DA #10 (Reid)

Designed C. Waters 9/19/12
Drawn C. Waters 9/19/12
Checked M. Allen 9/19/12
Approved D. Brinkmeyer 9/13

United States Department of Agriculture
Natural Resources Conservation Service
NRCS

File Name
IA346091912

Drawing Name
29-L-226

DA-313-A

BALTIMORE TWP T70N R5W
SECTION 25

N

Quincy Ave

Location Map

GEODE STATE PARK

0 1320 2640

Scale In Feet

If a cultural resource is identified during construction, stop immediately and notify the Natural Resources Conservation Service Archeologist at 515-284-4370

NRCS does not guarantee that this structure will fill and/or remain filled with water to the principal spillway crest elevation

CONTRACTOR IS RESPONSIBLE FOR CALLING IOWA ONE CALL 1-800-292-8989

All trees and shrubs shall be cleared and grubbed within a minimum distance of 30' from earthfill and spillway. New plantings shall not be made within these limitations.

AUXILIARY SPILLWAY
ELEV = 650.6
CONTROL SECTION = 35 FT
BOTTOM WIDTH = 18 FT
BERM HEIGHT = 2.0 FT
BERM TOP WIDTH = 8 FT
BERM LENGTH = 50 FT
ENTRANCE SLOPE = 3%
EXIT SLOPE = 4%
SIDE SLOPES = 3:1

PERMANENT POOL = 0.97 ac @ Elev 646.0

TBM @ Elev 648.60
On top of steel Rod

3% 3:1 4%

℄ 10" SMP

3:1

GEODE STATE PARK

50 0 50 100 150 200

N

PLAN VIEW

ENGINEERING JOB CLASS III

Designed L. Waters 10/8/12
Drawn C. Waters 10/8/12
Traced L. Waters 10/8/12
Checked M. Allred 3/13

Approved D. Eismeyer 3/13 DC

U.S. DEPARTMENT OF AGRICULTURE - NATURAL RESOURCES CONSERVATION SERVICE

DA #12 (Reid)
Grade Stabilization - H70
Baltimore TWP Section 25
T70N - R5W Henry Co. Iowa.

CAD FILE NAME



3- 60" x 60" Anti- seep collars
Length of pipe = 143 ft

SECTION ON CENTERLINE
Not to Scale

BILL OF MATERIALS

143 ft. of 10" dia 14" gage metal pipe with ~~hood~~ canopy inlet. Pipe and appurtenances to be welded and water tight at the seams.

3 ea. antiseep collars 60" x 60", 14" ga. 2 piece. Pipe connectors smooth metal

10,296 cu. yd. earth fill
Earthwork includes mainfill, dike, core trench, wave berm (eye brow), and stripping.

Approved D. Grossinger 9/13 Title PC
Designed C Waters 10/8/12 Drawn C Waters 10/8/12 Traced G. Wilcox 10/8/12 Checked M. Allen 9/13



NRCS does not guarantee that this structure will fill and/or remain filled with water to the principal spillway crest elevation

Cross Section

TBM = On top of Steel Rod @ Elev 648.6
Located in Fenceline Northeast of Dam site

Scale: 25' Date: 9/13 Designed: Canopy HOOD INLET Drawn: DA #12 - Reid Traced: Henry Checked:
U.S. DEPARTMENT OF AGRICULTURE - NATURAL RESOURCES CONSERVATION SERVICE

STANDARD DRAWING
Canopy ~~HOOD~~ INLET
STANDARD DWG. NO. 713
REVISED SHEET 1 OF 1



BENDING DIAGRAM FOR
(b) AND (c) RODS

BENDING DIAGRAM FOR
(d) BARS



BENDING DIAGRAM FOR
(a) RODS



ELEVATION

Pipe Diam. In.	Pipe Grade %	W In.	L In.	h Deg.	h Ft.
6	0-5	1 1/8	3 1/4	56	0.9
	5.1-15	1 1/4	4 3/4	45	0.9
	15.1-25	1 5/8	6 5/8	33	0.9
	25.1-32	2 1/8	7 3/4	27	0.9
8	0-5	1 1/2	4 3/8	56	1.2
	5.1-15	1 5/8	6 3/8	45	1.2
	15.1-25	2 1/8	8 3/4	33	1.2
	25.1-32	2 3/4	10 3/8	27	1.2
10	0-5	1 7/8	5 3/8	56	1.5
	5.1-15	2	8	45	1.5
	15.1-25	2 5/8	11	33	1.5
	25.1-32	3 1/2	13	27	1.5
12	0-5	2 1/4	6 1/2	56	1.8
	5.1-15	2 3/8	9 5/8	45	1.8
	15.1-25	3 1/4	13 1/4	33	1.8
	25.1-32	4 1/4	15 5/8	27	1.8
15	0-5	2 7/8	8 1/8	56	2.3
	5.1-15	3	12	45	2.3
	15.1-25	4	16 1/2	33	2.3
	25.1-32	5 1/4	19 1/2	27	2.3
18	0-5	3 3/8	9 3/4	56	2.7
	5.1-15	3 5/8	14 3/8	45	2.7
	15.1-25	4 7/8	19 3/4	33	2.7
	25.1-32	6 1/4	23 3/8	27	2.7
24	0-5	4 1/2	13	56	3.6
	5.1-15	4 3/4	19 1/4	45	3.6
	15.1-25	6 1/2	26 3/8	33	3.6
	25.1-32	8 3/8	31 1/4	27	3.6





DETAIL OF CANOPY INLET



* Minimum height for full pipe flow.

CANOPY INLET DIMENSIONS



PARTIAL ISOMETRIC VIEW

TABLE OF DIMENSION AND QUANTITIES

PIPE O.D. IN.	APPROX. WEIGHT LBS	(a) ROD SIZE IN.	H IN.	R IN.	X IN.	D IN.	TOTAL LENGTH IN.	NUMBER REQ'D	N IN.	(b) ROD SIZE IN.	r IN.	LENGTH IN.	NUMBER REQ'D	(c) ROD SIZE IN.	r IN.	LENGTH IN.	NUMBER REQ'D	(d) BAR SIZE IN.	r IN.	LENGTH IN.	NUMBER REQ'D
6	18.9	3/8	9	4	6	9 1/2	33	14	4	3/8	8 1/4	51 7/8	3	---	---	---	0	2 X 1/4	3 3/8	26 1/4	1
8	22.9	3/8	11	4 1/2	6	10 1/2	39	10	6 1/4	3/8	9 1/4	58 1/8	3	---	---	---	0	2 X 1/4	4 3/8	32 1/2	1
10	24.7	3/8	13	5 1/2	6	11 1/2	42	10	7	3/8	10 1/4	64 3/8	3	---	---	---	0	2 X 1/4	5 3/8	38 3/4	1
12	27.1	3/8	15	5 1/2	6	12 1/2	45	10	7 1/2	3/8	11 1/4	70 5/8	3	---	---	---	0	2 X 1/4	6 3/8	45	1
14	48.4	1/2	17	6	6	14	48	10	8 1/8	1/2	12	75 3/8	3	1/2	5	31 3/8	1	2 X 1/4	7 1/2	52 1/8	1
16	52.4	1/2	19	6 1/2	6	15	51	10	8 3/4	1/2	13	81 5/8	3	1/2	6	37 5/8	1	2 X 1/4	8 1/2	58 3/8	1
18	69.5	1/2	22	8 1/2	9	19 1/2	60	12	9 1/2	1/2	17	106 3/4	3	1/2	7	44	1	2 X 1/4	9 1/2	64 5/8	1
20	112.4	5/8	25	9	9	20 1/2	66	12	10	5/8	17 3/4	111 1/2	3	5/8	8	50 1/4	1	2 X 1/4	10 5/8	71 3/4	1
22	118.1	5/8	28	10	9	22	69	12	10 1/2	5/8	18 3/4	117 3/4	3	5/8	8	50 1/4	1	2 X 1/4	11 5/8	78	1
24	124.6	5/8	30	10 1/2	9	23	72	12	11	5/8	19 3/4	124	3	5/8	9 3/8	58 7/8	1	2 X 1/4	12 5/8	84 3/8	1

DA #12 - Reid
Grade stabilization - 410
25. Danville T70N-R5W

U.S. DEPARTMENT OF AGRICULTURE
NATURAL RESOURCES CONSERVATION SERVICE

Designed C. Waters 10/8/12
Drawn C. Waters 10/8/12
Traced C. Waters 10/8/12
Checked D Ensminger 4/13

Approved by D Ensminger
Title DE

Sheet No. 7 of 9

291.226



STEEL PLATE ANTI-SEEP COLLAR

NOTES:
1. All welds shall be watertight.
2. All steel plates shall have a minimum thickness of 1/4". Smooth Metal

4/04

NOT TO SCALE

Landowner:

Designed C. Waters 10/8/12
Drawn C. Waters 10/8/12
Checked M. Allen 1 3/13
Approved D. Eastman per 4/13

STEEL PLATE
ANTI-SEEP COLLAR DETAILS
DA # 12 (Reid)

United States Department of Agriculture
Natural Resources Conservation Service
NRCS

File Name

Drawing Name
29-L-226

IA-313-A





If a cultural resource is identified during construction, stop immediately and notify the Natural Resources Conservation Service Archeologist at 515-284-4370

NRCS does not guarantee that this structure will fill and/or remain filled with water to the principal spillway crest elevation

CONTRACTOR IS RESPONSIBLE FOR CALLING IOWA ONE CALL 1-800-292-8989

All trees and shrubs shall be cleared and grubbed within a minimum distance of 30' from earthfill and spillway. New plantings shall not be made within these limitations.



ENGINEERING JOB CLASS IV

PLAN VIEW

	Date
Approved	
Title	
Designed	C. Waters 9/19/12
Drawn	C. Waters 9/19/12
Traced	C. Waters 9/19/12
Checked	[illegible] 9/19/12

U.S. DEPARTMENT OF AGRICULTURE – NATURAL RESOURCES CONSERVATION SERVICE

DA # 9 - Reid
Grade Stabilization - 410
Baltimore TWP Section 25
T70N - R5W Henry Co. Iowa

CAD FILE NAME



2 - 72" x 72" Anti-seep collars
Length of pipe = 127 ft

SECTION ON CENTERLINE
Not to Scale

BILL OF MATERIALS

134 ft. of 12" dia 1/4" smooth ~~corge~~ metal pipe with ~~fixed~~ canopy inlet.
Pipe and appurtenances to be welded and water tight at seams.

2 ea. antiseep collars 72" x 72", 11" ga. 2 piece.
Pipe connectors smooth metal

9,751 cu. yd. earth fill
Earthwork includes mainFill, dike, core trench, wave berm (eye brow), and stripping

Designed L Waters 9/19/12
Drawn C Waters 9/19/12
Traced C Waters 9/19/12
Checked M Allen 3/13



Cross Section

TBM - On top of Steel Rod
Located West of Site in fenceline
@ Elev - 701.20

NRCS does not guarantee that this structure will fill and/or remain filled with water to the principal spillway crest elevation

Sheet 25 of 34 Sheets
County Henry
Canopy ~~HOOD~~ INLET
Cooperator DA # 9 - Reid

U.S. DEPARTMENT OF AGRICULTURE - NATURAL RESOURCES CONSERVATION SERVICE

STANDARD DWG. NO. 713
REVISED: SHEET 1 OF 1

31 of 34


LATERAL B
LATERAL E
LATERAL D
LATERAL C
LATERAL A
690.0
680.0
670.0
660.0
℄ FILL
CONSTRUCTED TOP OF FILL ELEV = 694.0
3
3
AUXILIARY SPILLWAY ELEV = 689.4
PIPE OUTLET ELEV = 665.0
CORE TRENCH
BOTTOM WIDTH = 12 FT
SIDE SLOPES = 1.5:1
MINIMUM DEPTH = 4 FT
AND TO SUITABLE MATERIAL
DOWNSTREAM TOE ELEV = 664.0
10+00
7+50
5+00
2+50
0+00
PROFILE
NRCS does not guarantee that this structure will fill and/or remain filled with water to the principal spillway crest elevation
Designed C. Waters 9/19/12
Drawn C. Waters 9/19/12
Traced C. Waters 9/19/12
Checked D. Ensminger 9/19/12
DA # 9 (Reid)
Grade Stabilization - 410
Baltimore Twp. Section 25
T80N R5W Hdrg Co. Iowa
NRCS DES MOINES, IOWA - NATURAL RESOURCES CONSERVATION SERVICE - U.S. DEPARTMENT OF AGRICULTURE
32 of 34



BENDING DIAGRAM FOR ⓑ AND ⓒ RODS

BENDING DIAGRAM FOR ⓓ BARS

Pipe Diam. In.	Pipe Grade %	W In.	L In.	θ Deg.	h Ft.
6	0-5	1 1/8	3 1/4	56	0.9
	5.1-15	1 1/4	4 3/4	45	0.9
	15.1-25	1 5/8	6 5/8	33	0.9
	25.1-32	2 1/8	7 3/4	27	0.9
8	0-5	1 1/2	4 3/8	56	1.2
	5.1-15	1 5/8	6 3/8	45	1.2
	15.1-25	2 1/8	8 3/4	33	1.2
	25.1-32	2 3/4	10 3/8	27	1.2
10	0-5	1 7/8	5 3/8	56	1.5
	5.1-15	2	8	45	1.5
	15.1-25	2 5/8	11	33	1.5
	25.1-32	3 1/2	13	27	1.5
12	0-5	2 1/4	6 1/2	56	1.8
	5.1-15	2 3/8	9 5/8	45	1.8
	15.1-25	3 1/4	13 1/4	33	1.8
	25.1-32	4 1/4	15 5/8	27	1.8
15	0-5	2 7/8	8 1/8	56	2.3
	5.1-15	3	12	45	2.3
	15.1-25	4	16 1/2	33	2.3
	25.1-32	5 1/4	19 1/2	27	2.3
18	0-5	3 3/8	9 3/4	56	2.7
	5.1-15	3 5/8	14 3/8	45	2.7
	15.1-25	4 7/8	19 3/4	33	2.7
	25.1-32	6 1/4	23 3/8	27	2.7
24	0-5	4 1/2	13	56	3.6
	5.1-15	4 3/4	19 1/4	45	3.6
	15.1-25	6 1/8	26 3/8	33	3.6
	25.1-32	8 3/8	31 1/4	27	3.6



DETAIL OF CANOPY INLET



* Minimum height for full pipe flow.

CANOPY INLET DIMENSIONS



BENDING DIAGRAM FOR ⓐ RODS



ELEVATION



PLAN



PARTIAL ISOMETRIC VIEW

TABLE OF DIMENSION AND QUANTITIES

PIPE O.D. IN.	APPROX. WEIGHT LBS	ⓐ ROD SIZE IN.	H IN.	R IN.	X IN.	D IN.	TOTAL LENGTH IN.	NUMBER REQ'D	N IN.	ⓑ ROD SIZE IN.	r IN.	LENGTH IN.	NUMBER REQ'D	ⓒ ROD SIZE IN.	r IN.	LENGTH IN.	NUMBER REQ'D	ⓓ BAR SIZE IN.	r IN.	LENGTH IN.	NUMBER REQ'D
6	18.9	3/8	9	4	6	9 1/2	33	14	4	3/8	8 1/2	51 1/4	3	---	---	---	0	2 X 1/4	3 3/4	26 1/2	1
8	22.8	3/8	11	4 1/2	6	10 1/2	39	10	6 1/4	3/8	9 1/4	66 1/4	3	---	---	---	0	2 X 1/4	4 3/4	32 1/2	1
10	24.7	3/8	13	5 1/2	6	11 1/2	42	10	7	3/8	10 1/4	64 3/4	3	---	---	---	0	2 X 1/4	5 3/4	38 3/4	1
12	27.1	3/8	15	5 1/2	6	12 1/2	45	10	7 1/2	3/8	11 1/4	70 3/4	3	---	---	---	0	2 X 1/4	6 3/4	45	1
14	48.3	1/2	17	6	6	14	48	10	8 1/2	1/2	12	75 3/4	3	1/2	5	31 3/4	1	2 X 1/4	7 1/2	52 1/2	1
16	52.4	1/2	19	6 1/2	6	15	51	10	8 3/4	1/2	13	81 3/4	3	1/2	6	37 3/4	1	2 X 1/4	8 1/2	58 3/4	1
18	69.5	1/2	22	8 1/2	9	19 1/2	60	12	9 1/2	1/2	17	106 3/4	3	1/2	7	44	1	2 X 1/4	9 1/2	64 3/4	1
20	112.4	5/8	25	9	9	20 1/2	66	12	10	5/8	17 3/4	111 1/2	3	5/8	8	50 1/4	1	2 X 1/4	10 3/4	71 3/4	1
22	118.1	5/8	28	10	9	22	69	12	10 1/2	5/8	18 3/4	117 3/4	3	5/8	8	50 1/4	1	2 X 1/4	11 3/4	78	1
24	124.6	5/8	30	10 1/2	9	23	72	12	11	5/8	19 3/4	124	3	5/8	9 3/4	58 7/8	1	2 X 1/4	12 3/4	84 3/4	1

DA#9 - Reid
35 Danville T7ON R5W

U.S. DEPARTMENT OF AGRICULTURE
NATURAL RESOURCES CONSERVATION SERVICE

Designed C.Waters 9/9/12
Drawn C.Waters 9/9/12
Traced C.Waters 9/9/12
Checked DBensinger 9/13

Approved by
Title
Date
Sheet No. 5 of 5

29L226



STEEL PLATE ANTI-SEEP COLLAR

NOTES:
1. All welds shall be watertight.
2. All steel plates shall have a minimum thickness of 1/4 ". Smooth Metal

4/04

NOT TO SCALE

Landowner:

STEEL PLATE
ANTI-SEEP COLLAR DETAILS
DA #9 (Reid)

		Date
Designed	L. Waters	3/13
Drawn	L. Waters	3/13
Checked	M. Allen	3/13
Approved	Engineer	4/13

United States Department of Agriculture
Natural Resources Conservation Service
NRCS

File Name
DA34609I912

Drawing Name
29-L-226